



GEORGE'S BIKE SHOP BALCATT'A

SPECS

FRAME	
SIZES	27.5: XS, S 29: S, M, L, XL
COLOURS	Knight Shield
FRAME	ALUXX grade aluminium
FORK	SR Suntour XCM30, QR, alloy steerer XS: 80mm travel (27.5) S: 80mm travel (27.5) / 100mm travel (29) M: 100mm travel (29), L: 100mm travel (29) XL: 100mm travel (29)
SHOCK	N/A
COMPONENTS	
HANDLEBAR	Giant Connect Trail, 31.8mm
GRIPS	Giant Sole-O
STEM	Giant Sport, 7-degree XS: 40mm (27.5) S: 50mm (27.5) / 50mm (29) M: 60mm (29) L: 70mm (29) XL: 80mm (29)
SEATPOST	Giant Sport, 30.9mm
SADDLE	Giant custom
PEDALS	MTB caged
DRIVETRAIN	
SHIFTERS	Shimano Altus M2010, 2x9
FRONT DERAILLEUR	Shimano Altus M2020
REAR DERAILLEUR	Shimano Altus M2000
BRAKES	Tektro TDK143, hydraulic, Tektro rotors [F]180mm, [R]160mm
BRAKE LEVERS	Tektro TDK143
CASSETTE	Shimano Deore HG200, 11x32
CHAIN	KMC X9
CRANKSET	ProWheel Forged, 22/36 XS: 165mm (27.5) S: 170mm (27.5) / 170mm (29) M: 175mm (29), L: 175mm (29) XL: 175mm (29)
BOTTOM BRACKET	Cartridge
WHEELS	
RIMS	Giant GX03V 29 or 27.5, alloy, double wall
HUBS	Alloy, sealed bearing
SPOKES	Stainless, 14g
TIRES	Kenda Booster 27.5 or 29x2.2", wire bead
EXTRAS	2.4" max tyre size, 32t max chainring size

FEATURES

- Frame: ALUXX grade aluminium
- Fork: SR Suntour XCM30, QR, alloy steerer XS: 80mm travel (27.5) S: 80mm travel (27.5) / 100mm travel (29) M: 100mm travel (29), L: 100mm travel (29) XL: 100mm travel (29)
- Shifters: Shimano Altus M2010, 2x9
- Crankset: ProWheel Forged, 22/36 XS: 165mm (27.5) S: 170mm (27.5) / 170mm (29) M: 175mm (29), L: 175mm (29) XL: 175mm (29)
- Colours: Knight Shield, Phantom Green

Price: \$949 RRP

GEOMETRY

FRAME	XS (27.5")	S (27.5")	S (29")	M (29")	L (29")	XL (29")
Seat Tube Length (mm)	350	385	390	440	490	535
Seat Tube Angle	74.0°	74.0°	74.0°	74.0°	74.0°	74.0°
Top Tube Length (mm)	544	569	577	599	620	639
Head Tube Length (mm)	95	115	95	105	125	140
Head Tube Angle	67.5°	67.5°	68.5°	68.5°	68.5°	68.5°
Fork Rake (mm)	42	42	51	51	51	51
Trail (mm)	103	103	94	94	94	94
Wheelbase (mm)	1079	1106	1126	1150	1172	1192
Chain Stay Length (mm)	440	440	455	455	455	455
Bottom Bracket Drop (mm)	45	45	55	55	55	55
Stack (mm)	533	571	602	611	630	644
Reach (mm)	385	405	404	424	439	454
Stand Over Height (mm)	686	711	732	766	805	839
Stem Length (mm)	40	50	50	60	70	80
Crank Length (mm)	165	170	170	175	175	175
Wheel Size	27.5"	27.5"	29"	29"	29"	29"

Please note that our specifications may be impacted by running substitution changes, we highly recommend confirming the specifications of our products with your local retailer at the time of sale if purchasing in-store. *Recommended Retail Prices are subject to change without notice and may vary from store to store depending on freight and assembly costs.