



## GEORGE'S BIKE SHOP BALCATTÀ

### SPECS

FRAME	
SIZES	S, M, L, XL
COLOURS	Phantom Green / Black / Chrome
FRAME	ALUXX SL-Grade aluminium front and rear triangles, 120mm Maestro suspension, flip chip, UDH hanger, 12x148mm thru-axle, 55mm Chainline
FORK	Fox 34 Performance, 130mm, GRIP damper, Boost 15x110 Kabolt, 44mm offset, custom tuned for Giant
SHOCK	Fox Float DPS Performance, custom tuned for Giant
COMPONENTS	
HANDLEBAR	Giant Contact TR35, alloy, 35mm
GRIPS	Giant Tactal Pro Single lock-on
STEM	Giant Contact SL 35 S:40mm, M:40mm, L:50mm, XL:50mm
SEATPOST	Giant Contact Switch dropper, remote S: 125mm travel / 30.9 x 395mm M: 150mm travel / 30.9 x 440mm L: 170mm travel / 30.9 x 450mm XL: 170mm travel / 30.9 x 450mm
SADDLE	Giant Romero
PEDALS	N/A
DRIVETRAIN	
SHIFTERS	Shimano SLX SL-M7100, 1x12
FRONT DERAILLEUR	N/A
REAR DERAILLEUR	Shimano SLX RD-M7100
BRAKES	Tektro Orion 4 Piston Hydraulic, Shimano RT-56 rotors [F]180mm, [R]180mm
BRAKE LEVERS	Tektro Orion
CASSETTE	Shimano SLX, 10x51
CHAIN	KMC X-12
CRANKSET	Shimano SLX, 30t S:165mm, M:170mm, L:170mm, XL:170mm
BOTTOM BRACKET	Shimano, press fit
WHEELS	
RIMS	Giant AM 29 tubeless ready sleeve-joint rim, 30mm inner width
HUBS	Alloy, sealed
SPOKES	Sapim
TIRES	[F] Maxxis Minion DHF 29x2.5 WT, 3C MaxxTerra, EXO, TR [R] Maxxis Aggressor 29x2.5, EXO, TR, tubeless
EXTRAS	Tubeless prepared, 2.6" max tyre size, 34t max chainring size

### FEATURES

- Frame: ALUXX SL-Grade aluminium front and rear triangles, 120mm Maestro suspension, flip chip, UDH hanger, 12x148mm thru-axle, 55mm Chainline
- Fork: Fox 34 Performance, 130mm, GRIP damper, Boost 15x110 Kabolt, 44mm offset, custom tuned for Giant
- Shifters: Shimano SLX SL-M7100, 1x12
- Crankset: Shimano SLX, 30t S:165mm, M:170mm, L:170mm, XL:170mm
- Colours: Phantom Green / Black / Chrome

Price: \$4,799 RRP

### GEOMETRY

FRAME	S	M	L	XL
	LOW   HIGH	LOW   HIGH	LOW   HIGH	LOW   HIGH
Seat Tube Length (mm)	420	430	465	496
Seat Tube Angle	77.2°   78.0°	76.3°   77.0°	76.3°   77.0°	76.3°   77.0°
Top Tube Length (mm)	561   559	599   597	626   624	663   661
Head Tube Length (mm)	100	110	120	130
Head Tube Angle	65.4°   66.2°	65.5°   66.2°	65.5°   66.2°	65.5°   66.2°
Fork Rake (mm)	44	44	44	44
Trail (mm)	126   120	126   120	126   120	126   120
Wheelbase (mm)	1166   1165	1195   1194	1224   1223	1263   1262
Chain Stay Length (mm)	439   437	439   437	439   437	439   437
Bottom Bracket Drop (mm)	45   35	45   35	45   35	45   35
Stack (mm)	610   604	619   613	628   622	637   631
Reach (mm)	422   431	447   456	472   480	507   515
Stand Over Height (mm)	730   738	725   734	749   759	771   780
Stem Length (mm)	40	40	50	50
Crank Length (mm)	165	170	170	170
Wheel Size	29"	29"	29"	29"

Please note that our specifications may be impacted by running substitution changes, we highly recommend confirming the specifications of our products with your local retailer at the time of sale if purchasing in-store. \*Recommended Retail Prices are subject to change without notice and may vary from store to store depending on freight and assembly costs.