



GEORGE'S BIKE SHOP BALCATTÀ

SPECS

FRAME	
SIZES	S, M, L, XL
COLOURS	Panther / Phantom Green / Chrome
FRAME	ALUXX SL-Grade Aluminium front and rear triangles, 135mm Maestro suspension, flip chip, 12x148mm thru-axle
FORK	Fox 36 Float Performance, FIT4, 44mm offset, 150mm, 15x110 Kabolt, custom tuned for Giant
SHOCK	Fox Float DPS Performance, custom tuned for Giant
COMPONENTS	
HANDLEBAR	Giant Contact SLR TR35, composite, 35mm
GRIPS	Giant Tactal Pro Single lock-on
STEM	Giant Contact SL 35 S:40mm, M:40mm, L:50mm, XL:50mm
SEATPOST	Giant Contact Switch dropper, remote
SADDLE	Giant Romero
PEDALS	N/A
DRIVETRAIN	
SHIFTERS	Shimano SLX SL-M7100, 1x12
FRONT DERAILLEUR	N/A
REAR DERAILLEUR	Shimano SLX RD-M7100
BRAKES	Tektro Orion 4 Piston, hydraulic, Shimano RT-66 rotors [F]203mm, [R]180mm
BRAKE LEVERS	Tektro Orion
CASSETTE	Shimano SLX, 10x51
CHAIN	KMC X-12
CRANKSET	Shimano M511, 30t S:165mm, M:170mm, L:170mm, XL:170mm
BOTTOM BRACKET	Shimano, press fit
WHEELS	
RIMS	Giant AM 29, alloy
HUBS	Alloy, sealed bearing
SPOKES	Sapim
TIRES	[F] Maxxis Minion DHF 29x2.5 WT, EXO, TR [R] Maxxis Aggressor 29x2.4, EXO, TR, tubeless
EXTRAS	Tubeless prepared, 2.5" max tyre size, 34t max chainring size

FEATURES

- Frame: ALUXX SL-Grade Aluminium front and rear triangles, 135mm Maestro suspension, flip chip, 12x148mm thru-axle
- Fork: Fox 36 Float Performance, FIT4, 44mm offset, 150mm, 15x110 Kabolt, custom tuned for Giant
- Shifters: Shimano SLX SL-M7100, 1x12
- Crankset: Shimano M511, 30t S:165mm, M:170mm, L:170mm, XL:170mm
- Colours: Panther / Phantom Green / Chrome

Price: \$5,199 RRP

GEOMETRY

FRAME	S	M	L	XL
	LOW HIGH	LOW HIGH	LOW HIGH	LOW HIGH
Seat Tube Length (mm)	430	430	465	496
Seat Tube Angle	77.2° 77.9°	77.2° 77.9°	77.2° 77.9°	77.2° 77.9°
Top Tube Length (mm)	566 564	597 595	629 627	656 654
Head Tube Length (mm)	95	100	110	120
Head Tube Angle	65.5° 66.2°	65.5° 66.2°	65.5° 66.2°	65.5° 66.2°
Fork Rake (mm)	44	44	44	44
Trail (mm)	125.1 119.5	125.1 119.5	125.1 119.7	125.1 119.5
Wheelbase (mm)	1173	1205	1239	1268
Chain Stay Length (mm)	438	438	438	438
Bottom Bracket Drop (mm)	40	40	40	40
Stack (mm)	617	621	631	640
Reach (mm)	426	456	486	510
Stand Over Height (mm)	734	729	754	777
Stem Length (mm)	40	40	50	50
Crank Length (mm)	165	170	170	170
Wheel Size	29"	29"	29"	29"

Please note that our specifications may be impacted by running substitution changes, we highly recommend confirming the specifications of our products with your local retailer at the time of sale if purchasing in-store. *Recommended Retail Prices are subject to change without notice and may vary from store to store depending on freight and assembly costs.