TRANCE X 3

GEORGE'S BIKE SHOP BALCATTA

SPECS

FRAME	
SIZES	S, M, L, XL
COLOURS	Good Grey / Black
FRAME	ALUXX SL-Grade aluminium front and rear triangles, 145mm Maestro suspension, flip chip, UDH hanger, 12x148mm thru-axle, 55mm Chainline
FORK	RockShox Yari RC, Motion Control, DebonAir, 37mm offset, 160mm, 15x110 Stealth, custom tuned for Giant
SHOCK	Fox Float DPS Performance, custom tuned for Giant
COMPONENTS	
HANDLEBAR	Giant Contact TR35, alloy, 35mm
GRIPS	Giant Tactal Pro Single lock-on
STEM	Giant Contact SL 35 S:40mm, M:40mm, L:50mm, XL:50mm
SEATPOST	Giant Contact Switch dropper, remote S: 125mm travel / 30.9 x 395mm M: 150mm travel / 30.9 x 440mm L: 170mm travel / 30.9 x 450mm XL: 170mm travel / 30.9 x 450mm
SADDLE	Giant Romero
PEDALS	N/A
DRIVETRAIN	
SHIFTERS	Shimano Deore, 1x12
FRONT DERAILLEUR	N/A
REAR DERAILLEUR	Shimano Deore
BRAKES	Tektro Orion, hydraulic, Shimano RT-66 rotors [F]203mm,[R]180mm
BRAKE LEVERS	Tektro Orion
CASSETTE	Shimano Deore, 10x51
CHAIN	KMC X-12
CRANKSET	Praxis Cadet M24 HD, 32t S:165mm, M:170mm, L:170mm, XL:170mm
BOTTOM BRACKET	Praxis, press fit
WHEELS	
RIMS	Giant AM 27.5, alloy
HUBS	Alloy, sealed bearing
SPOKES	Sapim
TIRES	[F] Maxxis Assegai 27.5x2.6, 3C MaxxTerra, EXO, TR [R] Maxxis Minion DHRII 27.5x2.6, 3C MaxxTerra, EXO, TR, tubeless
EXTRAS	Tubeless prepared, 2.6" max tyre size, 34t max chainring size

FEATURES

- Frame: ALUXX SL-Grade aluminium front and rear triangles, 145mm Maestro suspension, flip chip, UDH hanger, 12x148mm thru-axle, 55mm Chainline
- Fork: RockShox Yari RC, Motion Control, DebonAir, 37mm offset, 160mm, 15x110 Stealth, custom tuned for Giant
- Shifters: Shimano Deore, 1x12
- Crankset: Praxis Cadet M24 HD, 32t S:165mm, M:170mm, L:170mm, XL:170mm
- Colours: Good Grey / Black

Price: $4,399 RRP

GEOMETRY

FRAME	S	M	L	XL
	LOW | HIGH	LOW | HIGH	LOW | HIGH	LOW | HIGH
Seat Tube Length (mm)	420	430	465	496
Seat Tube Angle	77.2° | 78.0°	76.3° | 77.0°	76.3° | 77.0°	76.3° | 77.0°
Top Tube Length (mm)	562 | 560	595 | 593	622 | 620	649 | 647
Head Tube Length (mm)	95	105	115	125
Head Tube Angle	63.7° | 64.5°	63.8° | 64.5°	63.8° | 64.5°	63.8° | 64.5°
Fork Rake (mm)	37	37	37	37
Trail (mm)	138 | 132	138 | 132	138 | 132	138 | 132
Wheelbase (mm)	1179 | 1177	1203 | 1202	1233 | 1231	1262 | 1260
Chain Stay Length (mm)	433 | 430	433 | 430	433 | 430	433 | 430
Bottom Bracket Drop (mm)	30 | 20	30 | 20	30 | 20	30 | 20
Stack (mm)	596 | 590	605 | 599	614 | 608	623 | 617
Reach (mm)	427 | 435	447 | 455	472 | 480	497 | 505
Stand Over Height (mm)	709 | 718	714 | 723	740 | 750	762 | 772
Stem Length (mm)	40	40	50	50
Crank Length (mm)	165	170	170	170
Wheel Size	27,5"	27,5"	27,5"	27,5"

*Please note that our specifications may be impacted by running substitution changes, we highly recommend confirming the specifications of our products with your local retailer at the time of sale if purchasing in-store. *Recommended Retail Prices are subject to change without notice and may vary from store to store depending on freighting and assembly costs.*