







DISC BRAKE MOUNT ADAPTER

For postmount caliper

Performance indicator	Fork and frame mount style		Disc brake rotor size						
			140 mm (SS)	160 mm (S)	180 mm (M)	203 mm (L)	NEW 220 mm (LL)		
	Front	Post mount	140 mm direct	Direct mount	ISMMA90F180PPC	-	-	-	
			160 mm direct	-	Direct mount	ISMMA90F180PPC	-	-	
			180 mm direct	-	-	Direct mount	ISMMA90F203PPM	-	
			203 mm direct	-	-	-	Direct mount	-	
		International A-standard	-	ISMMA90F160PS	-	-	-		
	Rear	Post mount	140 mm direct	Direct mount	ISMMA90R180PPC	-	-	-	
			160 mm direct	-	Direct mount	ISMMA90R180PPC	-	-	
			180 mm direct	-	-	Direct mount	ISMMA90R203PPM	-	
			203 mm direct	-	-	-	Direct mount	-	
		International A-standard	ISMMA90R140PS	ISMMA90R160PS	ISMMA90R180PS	-	-		
	Front	Post mount	140 mm direct	Direct mount	ESMMAF180PP2A	-	-	-	
			160 mm direct	-	Direct mount	ESMMAF180PP2A	ISMMAF203PPA	-	
			180 mm direct	-	-	Direct mount	ESMMAF203PPMA	ESMMAF220PPM	
			NEW 200 mm direct	-	-	-	ESMMAF203PPL2	ESMMAF220PPL	
			203 mm direct	-	-	-	Direct mount	ESMMAF220PPL2	
		International A-standard	-	ISMMAF160PSA	ISMMAF180PSA	ISMMAF203PSA	-		
	Rear	Post mount	140 mm direct	Direct mount	ESMMAF180PP2A	-	-	-	
			160 mm direct	-	Direct mount	ESMMAF180PP2A	ISMMAF203PPA	-	
			180 mm direct	-	-	Direct mount	ESMMAF203PPMA	ESMMAF220PPM	
			NEW 200 mm direct	-	-	-	ESMMAF203PPL2	ESMMAF220PPL	
			203 mm direct	-	-	-	Direct mount	ESMMAF220PPL2	
		International A-standard	-	ISMMAF140PDA	ISMMAF160PDA	-	-		
		Rear	Post mount	140 mm direct	Direct mount	ESMMAF180PP2A	-	-	-
				160 mm direct	-	Direct mount	ESMMAF180PP2A	ISMMAF203PPA	-
				180 mm direct	-	-	Direct mount	ESMMAF203PPMA	ESMMAF220PPM
NEW 200 mm direct	-		-	-	ESMMAF203PPL2	ESMMAF220PPL			
203 mm direct	-	-	-	Direct mount	ESMMAF220PPL2				
International A-standard	-	ISMMAF160PSA	ISMMAF180PSA	ISMMAF203PSA	-				
Flat mount	ISMMAF140PDA	ISMMAF160PDA	-	-	-				
	Front	Post mount	140 mm direct	Direct mount	ISMMAF180PP2A	-	-	-	
			160 mm direct	-	Direct mount	ISMMAF180PP2A	ISMMAF203PPA	-	
	Rear	Post mount	140 mm direct	Direct mount	ISMMAF180PP2A	-	-	-	
			160 mm direct	-	Direct mount	ISMMAF180PP2A	ISMMAF203PPA	-	
			180 mm direct	-	-	Direct mount	ISMMAF203PPMA	ISMMAF220PPM	
		NEW 200 mm direct	-	-	-	ISMMAF203PPL2	ISMMAF220PPL		
203 mm direct	-	-	-	Direct mount	ISMMAF220PPL2				
International A-standard	-	ISMMAF160PSA	ISMMAF180PSA	ISMMAF203PSA	-				
	Front	Post mount	140 mm direct	Direct mount	ISMMAF180PP2A	-	-	-	
			160 mm direct	-	Direct mount	ISMMAF180PP2A	ISMMAF203PPA	-	
	Rear	Post mount	140 mm direct	Direct mount	ISMMAF180PP2A	-	-	-	
			160 mm direct	-	Direct mount	ISMMAF180PP2A	ISMMAF203PPA	-	
			180 mm direct	-	-	Direct mount	ISMMAF203PPMA	ISMMAF220PPM	
		NEW 200 mm direct	-	-	-	ISMMAF203PPL2	ISMMAF220PPL		
203 mm direct	-	-	-	Direct mount	ISMMAF220PPL2				
International A-standard	-	ISMMAF160PSA	ISMMAF180PSA	ISMMAF203PSA	-				

*Only includes converter fixing bolt for mount thickness 25 mm. Refer to page 17 for bolts for different mount thicknesses.

For international A-standard caliper

Performance indicator	Fork and frame mount style		Disc brake rotor size				
			140 mm (SS)	160 mm (S)	180 mm (M)	203 mm (L)	NEW 220 mm (LL)
	Front	Post mount	-	-	ISMMAF180SPA	ISMMAF203SPA	-
			ISMMAF180SPA	ISMMAF203SPA	-	-	-
	Front	International A-standard	-	Direct mount	ISMMAF180SSA	ISMMAF203SSA	-
			ISMMAF180SSA	ISMMAF203SSA	-	-	-
	Rear	International A-standard	-	Direct mount	ISMMAF180SSA	ISMMAF203SSA	-
			ISMMAF180SSA	ISMMAF203SSA	-	-	-