



www.georgesbikeshop.com.au

SPECS

FRAME	
SIZES	S, M, L, XL
COLOURS	Black Diamond, Metal
FRAME	ALUXX SL-Grade Aluminium, 12x148mm thru-axle
FORK	Giant Crest 34 RCL, 130mm, 44mm offset, Boost 15x110
SHOCK	N/A
COMPONENTS	
HANDLEBAR	Giant Contact SL TR35
GRIPS	Giant Sole-O
STEM	Giant Contact SL 35 S:40mm, M:40mm, L:50mm, XL:50mm
SEATPOST	Giant Contact Switch dropper, remote S: 125mm travel / 30.9 x 395mm, M: 125mm travel / 30.9 x 395mm, L: 150mm travel / 30.9 x 440mm, XL: 170mm travel / 30.9 x 450mm
SADDLE	Giant Romero
PEDALS	N/A
DRIVETRAIN	
SHIFTERS	Shimano Deore M-4100, 1x10
FRONT DERAILLEUR	N/A
REAR DERAILLEUR	Shimano Deore M-5120
BRAKES	Tektro HDM 275, hydraulic, Tektro rotors [F]180mm, [R]180mm
BRAKE LEVERS	Tektro HDM 275
CASSETTE	Shimano Deore M4100, 11x46
CHAIN	KMC X10
CRANKSET	Shimano Deore, 30t
BOTTOM BRACKET	Shimano, threaded

WHEELS	
RIMS	Giant AM 29, tubeless ready sleeve-joint rim, 30mm inner width
HUBS	Alloy, sealed
SPOKES	Stainless
TIRES	[F] Maxxis Minion DHF, 29x2.5 WT, EXO/TR[R] Maxxis Aggressor, 29x2.5 WT, foldable, EXO/T
EXTRAS	Tubeless prepared, 2.5" max tyre size, 32t max chainring size

Price: \$1,899 RRP

GEOMETRY

FRAME	S	M	L	XL
Seat Tube Length (mm)	380	430	465	495
Seat Tube Angle	75.0°	75.0°	75.0°	75.0°
Top Tube Length (mm)	592	612	639	662
Head Tube Length (mm)	95	95	105	115
Head Tube Angle	66.0°	66.0°	66.0°	66.0°
Fork Rake (mm)	44	44	44	44
Trail (mm)	122	122	122	122
Wheelbase (mm)	1157	1177	1206	1230
Chain Stay Length (mm)	438	438	438	438
Bottom Bracket Drop (mm)	60	60	60	60
Stack (mm)	622	622	631	640
Reach (mm)	425	445	470	490
Stand Over Height (mm)	727	746	764	791
Stem Length (mm)	40	40	50	50
Crank Length (mm)	165	170	170	170
Wheel Size	29"	29"	29"	29"

Please note that our specifications may be impacted by running substitution changes, we highly recommend confirming the specifications of our products with your local retailer at the time of sale if purchasing in-store. *Recommended Retail Prices are subject to change without notice and may vary from store to store depending on freight and assembly costs.