



www.georgesbikeshop.com.au

SPECS

HYBRID CYCLING TECHNOLOGY	
MOTOR	SyncDrive Pro, 85Nm, powered by Yamaha
CONTROLLER	RideControl Ergo 3, grip integrated
DISPLAY	RideControl GO, frame integrated LED display ANT+ Wireless display compatible
BATTERY	EnergyPak Smart 750, EnergyPak Plus 250Wh range extender compatible
FRAME	
SIZES	Cordovan
COLOURS	Cordovan/Copper Coin
FRAME	ALUXX SL-grade Aluminum, Advanced Forged Composite linkage, 140mm Maestro Suspension System, 'Boost' 148x12 UDH rear axle, Giant EnergyPak Plus Range Extender Compatible
FORK	RockShox 35 Gold RL DebonAir, 150mm travel, 44mm offset, MotionControl™ rebound and lockout control, 15x110 Boost, Maxle Stealth, e-MTB optimized
SHOCK	Rock Shox Deluxe Select R, DebonAir, 185x52.5mm Trunion mount, custom tuned
COMPONENTS	
HANDLEBAR	Giant Contact 35 Trail
GRIPS	Giant New trail grip Half-waffle/single lock-on
STEM	Giant Contact SL 35
SEATPOST	Giant Contact Switch dropper, remote S: 125mm travel / 30.9 x 395mm, M: 150mm travel / 30.9 x 440mm, L: 170mm travel / 30.9 x 450mm, XL: 170mm travel / 30.9 x 450mm
SADDLE	Giant Romero E
PEDALS	Flat pedals
DRIVETRAIN	
SHIFTERS	Shimano Deore
FRONT DERAILLEUR	MRP HD2 co-moulded chain guide
REAR DERAILLEUR	Shimano Deore, 12-speed
BRAKES	Shimano BR-M420, 4-piston, hydraulic disc, 203mm
BRAKE LEVERS	Shimano Deore, I-spec EV
CASSETTE	Shimano CS-M6100-12, 10-51T, 12-speed
CHAIN	KMC e.12 Turbo, EcoProteq, e-bike optimized
CRANKSET	Praxis Wave 36T Cold Forged 4130 premium steel Praxis e-Cadet+ custom forged crankarm set (Q-factor=168, S:160, M/L:165, XL:170)
BOTTOM BRACKET	N/A

WHEELS	
RIMS	Giant AM 29"
HUBS	Shimano MT410 Boost, Center-Lock, [F] 110x15 [R] 148x12mm Micro-Spline Drive Body Thru-axle
SPOKES	Sapim E-Lite [R] Race [F], e-bike optimized
TIRES	Maxxis Minion DHF 29x2.6" foldable, Tubeless, EXO+, 3C MaxxTerra [F] Maxxis Dissector 29x2.6" Foldable, Tubeless, EXO+, 3C MaxxTerra [R]
EXTRAS	Tubeless kit (liquid, valves, levers)
ACCESSORIES	
LOCK	Torx 25 Battery Lock with built-in Torque limiter

Price: \$7,999 RRP

GEOMETRY

FRAME	S		M		L		XL	
	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH
Seat Tube Length (mm)	400	425	450	475				
Seat Tube Angle	76.0° 76.7°	76.0° 76.7°	76.0° 76.7°	76.0° 76.7°	76.0° 76.7°	76.0° 76.7°	76.0° 76.7°	76.0° 76.7°
Top Tube Length (mm)	577 575	610 605	637 635	667 665				
Head Tube Length (mm)	95	100	110	120				
Head Tube Angle	65.7° 66.5°	65.8° 66.5°	65.8° 66.5°	65.8° 66.5°	65.8° 66.5°	65.8° 66.5°	65.8° 66.5°	65.8° 66.5°
Fork Rake (mm)	44	44	44	44				
Trail (mm)	117 122.4	117 122.4	117 122.4	117 122.4				
Wheelbase (mm)	1205 1206	1239 1237	1268 1269	1300 1301				
Chain Stay Length (mm)	473 473	473 473	473 473	473 473				
Bottom Bracket Drop (mm)	30 20	30 20	30 20	30 20				
Stack (mm)	606 601	611 605	621 614	630 624				
Reach (mm)	439 447	457 462	482 489	510 517				
Stand Over Height (mm)	783 789	775 784	763 770	775 782				
Stem Length (mm)	40	50	50	60				
Crank Length (mm)	160	165	165	170				
Wheel Size	29"	29"	29"	29"				

Please note that our specifications may be impacted by running substitution changes, we highly recommend confirming the specifications of our products with your local retailer at the time of sale if purchasing in-store. *Recommended Retail Prices are subject to change without notice and may vary from store to store depending on freight and assembly costs.