



WWW.GEORGESBIKESHOP.COM.AU

SPECS

FRAME	
SIZES	29: S, M, L, XL
COLOURS	Metallic Black, Cobalt
FRAME	ALUXX-grade aluminum, disc
FORK	SR Suntour XCE, QR, alloy steerer S: 100mm travel (29) M: 100mm travel (29), L: 100mm travel (29) XL: 100mm travel (29)
SHOCK	N/A
COMPONENTS	
HANDLEBAR	Giant Connect Trail, 31.8mm
GRIPS	Giant Sole-O
STEM	Giant Sport, 7-degree S: 50mm (29) M: 60mm (29) L: 70mm (29) XL: 80mm (29)
SEATPOST	Giant Sport, 30.9mm
SADDLE	Giant
PEDALS	MTB caged
DRIVETRAIN	
SHIFTERS	microSHIFT TS39, 2x8
FRONT DERAILLEUR	microSHIFT FD-M282
REAR DERAILLEUR	Shimano Altus M310
BRAKES	Tektro HDC M275, hydraulic, Tektro rotors [F]180mm, [R]160mm
BRAKE LEVERS	Tektro HDC M275
CASSETTE	Shimano Deore HG200, 12x32
CHAIN	KMC 8.3
CRANKSET	Shimano FC-M315, 22/36 S: 170mm (29) M: 175mm (29), L: 175mm (29) XL: 175mm (29)
BOTTOM BRACKET	Cartridge

WHEELS

RIMS	Giant GX03V 29" alloy, double wall
HUBS	Alloy, sealed
SPOKES	Stainless, 14g
TIRES	Kenda Booster 29x2.2", wire bead
EXTRAS	2.4" max tyre size, 32t max chainring size

Price: \$899 RRP

GEOMETRY

FRAME	S (29")	M (29")	L (29")	XL (29")
Seat Tube Length (mm)	390	440	490	535
SeatpostInsertionDepth (mm)	245	200	250	300
Seat Tube Angle	74.0°	74.0°	74.0°	74.0°
Top Tube Length (mm)	577	599	620	639
Head Tube Length (mm)	95	105	125	140
Head Tube Angle	68.5°	68.5°	68.5°	68.5°
Fork Rake (mm)	51	51	51	51
Trail (mm)	94	94	94	94
Wheelbase (mm)	1126	1150	1172	1192
Chain Stay Length (mm)	455	455	455	455
Bottom Bracket Drop (mm)	55	55	55	55
Stack (mm)	602	611	630	644
Reach (mm)	404	424	439	454
Stand Over Height (mm)	732	766	805	839
Stem Length (mm)	50	60	70	80
Crank Length (mm)	170	175	175	175
Wheel Size	[F] 29" [R]	[F] 29" [R]	[F] 29" [R]	[F] 29" [R]

Please note that our specifications may be impacted by running substitution changes, we highly recommend confirming the specifications of our products with your local retailer at the time of sale if purchasing in-store. *Recommended Retail Prices are subject to change without notice and may vary from store to store depending on freight and assembly costs.