



WWW.GEORGESBIKESHOP.COM.AU

SPECS

FRAME	
SIZES	29": S, M, L
COLOURS	Sandshell
FRAME	ALUXX-grade aluminum, disc
FORK	SXC32-2 RL, air spring, QR, alloy steerer S: 100mm travel (29) M: 100mm travel (29) L: 100mm travel (29)
SHOCK	N/A
COMPONENTS	
HANDLEBAR	Giant Connect Trail, 31.8mm
GRIPS	Giant Sole-O
STEM	Giant Sport, 7-degree S: 40mm (29) M: 50mm (29) L: 50mm (29)
SEATPOST	Giant Sport, 30.9mm
SADDLE	Liv Sport
PEDALS	MTB caged
DRIVETRAIN	
SHIFTERS	Shimano CUES, SL-6000, 1x10
FRONT DERAILLEUR	N/A
REAR DERAILLEUR	Shimano CUES, U6000, Shadow+
BRAKES	Tektro HDC TKD 149, hydraulic, Tektro rotors [F]180mm, [R]160mm
BRAKE LEVERS	Tektro TKD 149
CASSETTE	Shimano CUES CS-LG300, 11x48
CHAIN	Shimano CUES LG500
CRANKSET	ProWheel Charm, 30t S: 170mm (29) M:170mm (29) L:170mm (29)
BOTTOM BRACKET	Cartridge

WHEELS	
RIMS	Giant GX03V 29 alloy, double wall
HUBS	Alloy, sealed
SPOKES	Stainless, 14g
TIRES	Kenda Booster 29x2.4", wire bead
EXTRAS	2.4" max tyre size, 32t max chainring size

Price: \$1,299 RRP

GEOMETRY

FRAME	S (29")	M (29")	L (29")
Seat Tube Length (mm)	370	420	450
SeatpostInsertionDepth (mm)	320	375	220
Seat Tube Angle	74.0°	74.0°	74.0°
Top Tube Length (mm)	570	590	610
Head Tube Length (mm)	90	95	105
Head Tube Angle	68.5°	68.5°	68.5°
Fork Rake (mm)	51	51	51
Trail (mm)	94.3	94.3	94.3
Wheelbase (mm)	1119	1139	1160
Chain Stay Length (mm)	455	455	455
Bottom Bracket Drop (mm)	55	55	55
Stack (mm)	596	601	610
Reach (mm)	399	418	435
Stand Over Height (mm)	705	737	757
Stem Length (mm)	40	50	50
Crank Length (mm)	170	170	175
Wheel Size	29"	29"	29"

Please note that our specifications may be impacted by running substitution changes, we highly recommend confirming the specifications of our products with your local retailer at the time of sale if purchasing in-store. *Recommended Retail Prices are subject to change without notice and may vary from store to store depending on freight and assembly costs.