



SPECS

HYBRID CYCLING TECHNOLOGY	
MOTOR	SyncDrive Pro 2, 85Nm, powered by Yamaha
CONTROLLER	RideControl Ergo 3, grip integrated
DISPLAY	RideControl GO, frame integrated LED display ANT+ Wireless display compatible
BATTERY	EnergyPak Smart 800Wh EnergyPak Plus range extender compatible
CHARGER	EnergyPak 6A smart charger
CONNECTIVITY	Giant RideControl App enabled ANT+ wireless display signal with e-bike profile
FRAME	
SIZES	S, M, L, XL
COLOURS	Raw Aluminium
FRAME	ALUXX SL-grade Aluminium, Advanced Forged Composite Upper Rocker, 160mm Maestro suspension system, flip chip, UDH hanger 12x148mm thru-axle
FORK	SR Suntour DuroLux 38 Boost EQ, 170mm travel, 44mm offset, RC2, 15LH-110
SHOCK	Fox Float DPS Performance, EVOL Large Volume sleeve, custom tuned
COMPONENTS	
HANDLEBAR	Giant Contact Trail, 35mm
GRIPS	Giant Tactal Pro-E, single lock-on
STEM	Giant Contact SL 35mm S:40mm, M:40mm, L:40mm, XL:50mm
SEATPOST	Giant Contact Switch travel-adjustable dropper, remote S: 110-140mm travel / 30.9 x 395mm M: 140-170mm travel / 30.9 x 470mm L: 170-200mm travel / 30.9 x 530mm XL: 170-200mm travel / 30.9 x 530mm
SADDLE	Giant Romero Trail
PEDALS	Platform
DRIVETRAIN	
SHIFTERS	Shimano CUES, SL-6000, 1x11
FRONT DERAILLEUR	MRP 1X HD2 custom co-molded chain guide
REAR DERAILLEUR	Shimano CUES, U6000, Shadow+
BRAKES	Shimano BR-MT420, 4-piston, hydraulic disc, 203mm
BRAKE LEVERS	Shimano Deore, I-spec EV
CASSETTE	Shimano Cues LinkGlide, CS-LG400-11, 11-50T, 11-speed
CHAIN	Shimano Cues CN-LG500
CRANKSET	Praxis Wave™ 36T Cold Forged 4130 premium steel Praxis e-Cadet+ custom forged crankarm set S:160mm, M: 160mm, L:165mm, XL:165mm
BOTTOM BRACKET	N/A

WHEELS	
RIMS	Giant AM 29" [F] 27.5" [R], Tubeless ready
HUBS	Shimano MT410, Boost, Center-Lock, [F] 110x15 [R] 148x12mm HG Drive Body Thru-axle
SPOKES	Sapim E-Lite [R] Race [F], e-bike optimised
TIRES	Maxxis Minion DHF 29x2.6" foldable, Tubeless, EXO+, 3C MaxxTerra [F] Maxxis High Roller II 27.5x2.5" foldable, Tubeless, DoubleDown, 3C MaxxTerra Compound [R]
EXTRAS	Tubeless kit (liquid, valves, levers, manual, tool)
ACCESSORIES	
LOCK	Torx 25 Battery Lock with built-in Torque limiter

Price: \$8,799.00

GEOMETRY

FRAME	S		M		L		XL	
	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH
Seat Tube Length (mm)	400	425	450	475				
Seat Post Insertion Depth (mm)	230	260	280	310				
Seat Tube Angle	76.7° 77.5°	76.7° 77.5°	76.7° 77.5°	76.7° 77.5°				
Top Tube Length (mm)	569 568	595 594	622 621	649 648				
Head Tube Length (mm)	100	100	110	120				
Head Tube Angle	63.7° 64.5°	63.7° 64.5°	63.7° 64.5°	63.7° 64.5°				
Fork Rake (mm)	44	44	44	44				
Trail (mm)	135.5 132.1	135 132	135 132	135.5 132.1				
Wheelbase (mm)	1209 1210	1236 1237	1265 1266	1295 1296				
Chain Stay Length (mm)	457 455	454 454	454 454	454 454				
Bottom Bracket Drop (mm)	25 15	25 15	25 15	25 15				
Stack (mm)	636 632	635 632	645 641	654 650				
Reach (mm)	425 430	450 455	475 480	500 505				
Stand Over Height (mm)	785 789	772 776	771 775	768 772				
Stem Length (mm)	40	40	40	50				
Crank Length (mm)	160	160	165	165				
Wheel Size	29"	[F] 29" [R]	[F] 29" [R]	[F] 29" [R]				

Please note that our specifications may be impacted by running substitution changes, we highly recommend confirming the specifications of our products with your local retailer at the time of sale if purchasing in-store. *Recommended Retail Prices are subject to change without notice and may vary from store to store depending on freight and assembly costs.