

TALON 4



WWW.GEORGESBIKESHOP.COM.AU

SPECS

FRAME	
SIZES	27.5: XS, S 29: S, M, L, XL
COLOURS	Cyber Lime
FRAME	ALUXX-Grade aluminium, disc
FORK	SR Suntour XCE 28, coil spring, QR, steel steerer XS: 80mm travel (27.5) S: 80mm travel (27.5) / 100mm travel (29) M: 100mm travel (29), L: 100mm travel (29) XL: 100mm travel (29)
SHOCK	N/A
COMPONENTS	
HANDLEBAR	Giant Connect Trail, 31.8mm
GRIPS	Giant Sole-O
STEM	Giant Sport, 7-degree XS: 40mm (27.5) S: 50mm (27.5) / 50mm (29) M: 60mm (29) L: 70mm (29) XL: 80mm (29)
SEATPOST	Giant Sport, 30.9mm
SADDLE	Giant Sport
PEDALS	MTB caged
DRIVETRAIN	
SHIFTERS	microSHIFT Acolyte, 1x8
FRONT DERAILLEUR	N/A
REAR DERAILLEUR	microSHIFT Acolyte, M5185M w/clutch
BRAKES	Tektro HD TKD-176, hydraulic, Tektro rotors [F]160mm, [R]160mm
BRAKE LEVERS	Tektro HD TKD-176
CASSETTE	microSHIFT Acolyte H083, 12x46
CHAIN	KMC 8.3
CRANKSET	ProWheel EPRO, 30t (29"), 32t (27.5") XS: 165mm (27.5) S: 165mm (27.5) / 170mm (29) M: 170mm (29) L: 170mm (29) XL: 175mm (29)
BOTTOM BRACKET	Cartridge

WHEELS	
RIMS	Giant GX03V 29 or 27.5, alloy, double wall, 28H
HUBS	Alloy, [F] 9mm QR, [R] 12x142 thru-axle
SPOKES	Stainless, 14g
TYRES	Maxxis Ikon 27.5" or 29x2.2", wire bead
LIMITS	
MAX TYRE CLEARANCE	2.4" max tyre size
MAX CHAINRING SIZE	32t max chainring size

Price: \$849.00

GEOMETRY

FRAME	XS (27.5")	S (27.5")	S (29")	M (29")	L (29")	XL (29")
Seat Tube Length (mm)	345	375	380	420	450	480
Seat Post Insertion Depth (mm)	300	340	245	200	250	300
Seat Tube Angle	74.0°	74.0°	74.5°	74.5°	74.5°	74.5°
Top Tube Length (mm)	542	562	581	604	629	653
Head Tube Length (mm)	90	90	95	105	125	140
Head Tube Angle	67.0°	67.0°	67.5°	67.5°	67.5°	67.5°
Fork Rake (mm)	44	44	44	44	44	44
Trail (mm)	105	105	109	109	109	109
Wheelbase (mm)	1084	1104	1140	1164	1191	1216
Chain Stay Length (mm)	440	440	455	455	455	455
Bottom Bracket Drop (mm)	45	45	55	55	55	55
Stack (mm)	548	548	597	606	625	638
Reach (mm)	385	405	415	435	455	475
Stand Over Height (mm)	684	684	715	708	708	710
Stem Length (mm)	40	50	40	50	60	60
Crank Length (mm)	165	165	170	170	170	175

Please note that our specifications may be impacted by running substitution changes, we highly recommend confirming the specifications of our products with your local retailer at the time of sale if purchasing in-store. *Recommended Retail Prices are subject to change without notice and may vary from store to store depending on freight and assembly costs.